


RETENTION DISK



SUBGRADE

TYPICAL ELEVATION VIEW

NOTES

- 1. TO PREVENT LOSS OF BONDING MATERIAL THE RETENTION DISK SHALL BE HELD IN PLACE WITH WOOD STAKES, REBARS, TAPE OR OTHER MEANS APPROVED BY THE ENGINEER.
- 2. A CHAIR OR OTHER ACCEPTABLE DEVICE SHALL BE USED TO MAINTAIN THE DOWEL OR TIE BAR IN A LEVEL HORIZONTAL POSITION. LEVELING DEVICES SHALL BE REMOVED AFTER THE BONDING MATERIAL HAS SET.
- 3. COST OF THE DOWEL OR TIE BAR. DRILLED HOLES, RETENTION DISK. LEVELING DEVICES. BONDING MATERIAL. ALL EQUIPMENT. TOOLS. AND LABOR SHALL BE INCIDENTAL TO THE RESPECTIVE TYPE 1 OR 2 REPAIR PAY ITEM IN THE INVITATION FOR BIDS.
- 4. BONDING MATERIAL PER 902.11.

4-18-90

10-1-01

APPROVAL

REVISED

REVISED

REVISED

6-8-90

APPROVAL

REVISED

REVISED

REVISED

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

DOWEL AND TIE BAR ANCHORAGE FOR TYPE 1 AND TYPE 2 PAVEMENT REPAIRS

STANDARD NO. MD 577.08